

Temporary energy, cooling, heating, oil-free air and power solutions

Power Generation and Energy Equipment

 Diesel Generators From 25 kW to 2000 kW	 Low-emissions Tier 4F Generators From 25 kW to 1200 kW	 Natural Gas Generators From 100 kW to 1500 kW	 Energy Storage From 24 kW to 1 MW batteries
 Fuel Flex 400 kW Gas Generator 379 kW continuous rating	 PowerFlex 1500 kW Gas Generator 1489 kW continuous power output	 1300 kW Rapid Deploy Gas Power Generation 1300 kW continuous power at a choice of 15 kV, 5 kV, or 480 kV	 Fuel Tanks 250-5000 gallon fuel tanks



Cooling

 Chillers From 10 to 1000 tons	 Cooling Towers From 200 to 1000 tons	 Air Conditioners From 1 to 70 tons	 Air Handlers From 10 to 140 tons	 Spot Coolers From 1 to 5 tons
--	---	---	---	--

Heating and Dehumidification

 Electric Heaters From 171,000 to 512,000 BTU/HR	 Indirect Heaters From 500,000 to 1.5 M BTU/HR	 Hydronic Heaters and Boilers From 900,000 to 1.8 M BTU/HR	 Dehumidifiers Desiccant with capabilities From 2000 to 15,000 cfm	 Pumps, Accessories, Hoses, Valves, Ducts From 100 to 12,000 gpm
--	--	--	--	--

Industrial Heat Exchangers

 Heat Exchangers From 500 to 5100 ft²	 Plate/Frame Heat Exchangers From 50 to 2000 ft²	 Food Grade Heat Exchangers From 600 to 1600 ft²	 Large Node Heat Exchangers From 5100 to 5700 ft²	 Hastelloy-C Cross-Flow Heat Exchanger 1500 ft²
--	---	---	---	--

Oil-Free Compressed Air

 100% Oil-Free Diesel Air From 1500 cfm and 1600 cfm, at max pressure of 150 psi	 100% Oil-Free Electric 400 cfm, 800 cfm, 1500 cfm and 1600 cfm, at max pressure of 150 psi	 Desiccant Dryers From 450 to 5400 cfm	 Accessories: hoses, fittings, manifolds, auxiliary fuel tanks, air receivers, pressure regulators, electric boosters
--	---	---	--

Load Banks

 Resistive From 100 kW to 5000 kW	 Resistive / Reactive From 240 kW - 6250 kW	 Capacitive 2000 kVAR	 Direct Current (DC) From 28 VDC to 700 VDC
--	--	---	--

Electrical Distribution

 Transformers Dry: 15 kVA – 5000 kVA Oil Filled: 300 kVA - 10 MVA	 I-line Panels From 225 – +6000 Amps	 Mill Panels / Low Voltage Distro Pack 30 kVA 480 V to 208 / 120 V, 3-Phase	 Breakers LV breakers, MV and Multi-gang breakers	 Starters Low voltage, medium voltage and soft starters
 Switches (Fused, Manual, & Automatic) LV: 100 – 4000 Amps / 208 – 600 V MV: 600 & 1200 Amps, 5 – 38 kV	 Motor Control Centers Size 00 – 6 starters, breaker or fused disc. style	 Variable Frequency Drives (VFDs) 40 HP – 900 HP	 Common Buss Cabinets LV: up to 10,000 Amps MV: up to 8000 Amps	Cable LV: up to #4/0, type W HV: up to #4/0, type SH (shielded) HV available in various lengths Special Occupancy Gear LV Class 1, Div 1 & 2, Grp B, C, D. Some gear available in NEMA 7. Some gear utilizes purge systems.